


Anchors Cross Plate

Coated (Less Rods)

Cross plate anchors are made for installation in holes drilled by power drillers. Cross plate anchors are formed of two structural steel plates that are ribbed for reinforcement.




Catalog No.	Hole Size (Inches)	Area (Sq. In.)	Rod Size (Inches) (Order Separately)	Holding Strength (Lbs.) Soil Class					Approximate Weight (Lbs. Each)
				3	4	5	6	7	
J3516	16	150	5/8 or 3/4	26,500	22,500	18,500	14,500	9,500	10
J3520	20	250	5/8 or 3/4	34,000	29,000	24,000	19,000	14,000	16
J3520-1	20	250	1	34,000	29,000	24,000	19,000	14,000	16
J3524-3/4	24	400	5/8 or 3/4	45,000	37,000	30,000	23,500	18,000	33
J3524	24	400	1	45,000	37,000	30,000	23,500	18,000	33
J3524-1	24	400	1-1/4	45,000	37,000	30,000	23,500	18,000	33

Anchors Pole Key (Expanding)

Coated

This expanding anchor keys poles at their butt to reinforce them against unbalanced loads in soft soils. Placed at the bottom of the hole, behind the pole, it is easily expanded into solid earth and eliminates the necessity for digging a trench for installing a wood key.



Catalog No.	Width Expanded (Inches)	Blade Width (Inches)	Area Expanded (Sq. In.)	Approximate Weight (Lbs. Each)
J4817	27-1/4	7	276	25