

# SOLUTIONS IN PLASTIC

Serving the Telecommunications, Electrical Utility, CATV and Data/Voice Industries

[Duct & Conduit](#)
[Electrical Pedestals](#)
[Markers & Crossarms](#)
[Specialty Products & Services](#)
[About Us](#)
[Home](#)

## LUBE Silicone Free

### PetroDuct™ Pre-Lube

Applied during extrusion, the exclusive PNA process pre-lubes duct with a high polarity polymeric lubricant. ProPull™ Pre-Lube is completely effective from 20°F to 250°. Pre-Lube will not harm HDPE or insulation on cable, and does not contain silicone.



### ProPull™ Cable Lubricant

ProPull™ cable lubricant provides non-separating disbursement in all sizes and shapes of duct. Its unique ionic polarity helps prevent friction and burn-through. These physical properties allow vertical pulls without losing effectiveness even in extreme temperatures (20° F to 250°). It will not evaporate, crystallize or deteriorate, and can be used in other duct material such as fiberglass and PVC. Virtually non-toxic and bio-degradable, ProPull™ Cable Lubricant does not contain silicone. MSDS [Page 1](#), [Page 2](#)



Available sizes include: Quarts, Half Gallons, Gallons, and 5 Gallon pails..

### Quantities of ProPull™ Lubricant in Gallons

Duct Size (in inches)	500 Feet	1000 Feet	2000 Feet	3000 Feet	4000 Feet	5000 Feet
1	.50	1.00	2.00	3.00	4.00	5.00
1-1/4	.60	1.25	2.50	3.75	5.00	6.25
1-1/2	.75	1.50	3.00	4.50	6.00	7.50
2	1.00	2.00	4.00	6.00	8.00	10.00
2-1/2	1.25	2.50	5.00	7.50	10.00	12.50
3	1.50	3.00	6.00	9.00	12.00	15.00
4	2.00	4.00	8.00	12.00	16.00	20.00
5	2.50	5.00	10.00	15.00	20.00	25.00
6	3.00	6.00	12.00	18.00	24.00	30.00

All Rights Reserved. PNA / API, Ltd©. 2005.  
Site design by [Ryan Belton](#)

