

SOLUTIONS IN PLASTIC

Serving the Telecommunications, Electrical Utility, CATV and Data/Voice Industries

Duct & Conduit

Electrical Pedestals

Markers & Crossarms

Specialty Products & Services

About Us

Home

PULL ROPE & TAPE



PNA supplies Polyester Pull Tape™ and ProPull™ Pull Rope to meet the strict requirements of all cable-in-conduit applications. All are available pre-installed in HDPE duct or may be purchased separately for pulling in the field. Because of a special pre-lubrication process, polyester tape features a lower coefficient of friction than competitors' brands costing much more. They also feature a much softer feel than stiff-coated competitive tapes, resulting in easier and more comfortable handling by linemen. Tape is available from 1,250 to 2,500 lbs. rated strength.

POLYESTER FIBER PULLTAPE™

Produced using high tensile, high tenacity, low shrink polyester fibers. This is the most competitively priced high tensile strength pull tape. This product is available with a silicone lubricant, which is compatible with the Lube used in the manufacture of the innerduct, and greatly reduces the possibility of burn-through. The tapes are also available with printed sequential footage markings for accurate measurements.

Part #	Construction	Tensile Lbs/Kg
WP900	Woven	900/40
WP1800	Woven	1800/816
WP4000	Woven	4000/1814
WP6000	Woven	6000/2722

ARAMID FIBER PULLTAPE™

Produced using high tensile, high strength Aramid yarns, these tapes offer the highest tensile strength per width along with low elongation. Aramid fibers limiting oxygen index (LOI) allows the tapes to be used in Plenum Duct applications, where flame resistant requirements exist. This product is also available with a silicone lubricant, which is compatible with the Lube used in the manufacture of the innerduct, and greatly reduces the possibility of burn-through. The tapes are also available with printed sequential footage markings for accurate measurements.

Part #	Construction	Tensile Lbs/Kg
WA900	Woven	900/408
WA1250	Woven	1250/567
WP1800	Woven	1800/816
WP2500	Woven	2500/1134

BLENDED FIBER PULLTAPE™

Developed primarily to give the same pulling properties as with

Tensile

the 100% Aramid construction, but at a lower cost. Aramid fibers are mechanically blended with high tenacity polyester fibers. These tapes are available with a silicone lubricant, which is compatible with the Lube used in the manufacture of the innerduct, and greatly reduces the possibility of burn-through. The tapes are also available with printed sequential footage markings for accurate measurements.	Part #	Construction	Lbs/Kg
	WB1250	Woven	1250/567
	WB1500	Woven	1500/680
	WB2000	Woven	2000/907
	WP2500	Woven	2500/1134

PULLTAPE™ IS A REGISTERED TRADEMARK OF FIBERTEK, INC.

All Rights Reserved. PNA / API, Ltd©. 2005.
 Site design by [Ryan Belton](#)

