

PHYSICAL PROPERTIES AND TYPICAL VALUES

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Thickness Overall	D-2103	3.0 MIL	0.08 MM
Weight	D-2103	15.0 LBS/1000 FT ²	7.3 KG/100 M ²
3" Tensile	D-882	24.5 LBF	109 N
		2700 PSI	18.6 MPA
Elongation	D-882	680 %	680 %
PPT Resistance	D-2582	13.5 LBF	60 N
Printability	D-2578	≥ 40 Dynes	≥ 40 Dynes

FEATURES

- Terra Tape® Economy is a pigmented polyolefin film with a printed message on one side used to protect, identify and locate underground utility lines.
- The ink used to print the material is permanent and cannot be removed by normal handling or upon long term underground burial.
- The material and ink are chemically inert and will not degrade when exposed to acids, alkalis and other destructive substances commonly found in soil.
- The material is available in red or yellow. Other colors may be available upon request.

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

TOLLFREE 1.800.231.6074

9209 Alameda Genoa Rd. • Houston, Texas 77075

P: 713.507.4251 • F: 713.507.4295

Des de Mexico 001.800.426.1447

Email: ri@reefindustries.com

