

PHYSICAL PROPERTIES AND TYPICAL VALUES

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Thickness Overall	D-2103	11.0 MIL	0.28 MM
Weight	D-2103	35.5 LBS/1000 FT ²	17.3 KG/100 M ²
3" Tensile	D-882	400 LBF	1780 N
		11300 PSI	77.9 MPA
Elongation	D-882	20 %	20 %
PPT Resistance	D-2582	50 LBF	222 N
Printability	D-2578	≥ 40 Dynes	≥ 40 Dynes

FEATURES

- Terra Tape® Extra Strength is a strong, tear resistant and tough reinforced marking tape designed not to stretch and to break cleanly without distortion when caught by an excavating backhoe.
- Extra Strength is a multi-layer laminate consisting of an HDPE scrim coated on both sides with 100% virgin polyolefin pigmented resins. A printed message is on one side and the product is used to protect, identify and locate underground utility lines.
- The ink used to print the material is permanent and cannot be removed by normal handling or upon burial.
- The material and ink are chemically inert and will not degrade when exposed to acids, alkalis and other destructive substances commonly found in soil.
- The material is available in the colors orange and yellow. Other colors may be available upon request.

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

TOLLFREE 1.800.231.6074

9209 Alameda Genoa Rd. • Houston, Texas 77075

P: 713.507.4251 • F: 713.507.4295

Des de Mexico 001.800.426.1447

Email: ri@reefindustries.com

