



[HOME](#) [PRODUCTS](#) [DISTRIBUTORS](#) [ABOUT US](#) [NEWS](#) [CONTACT](#)

Century Wire on the Move

Haga Clic Aquí
Para Español

Stainless Steel Wire Rope Products

» [PRODUCTS](#)

[Lashing Wire](#)

[Strand](#)

[Tie Wire](#)

[Safety Wire](#)

[Lockwire](#)

[Other Wire Available](#)

[Tools](#)

[Pipe/Valves](#)

[Safety Equipment](#)

.....
Century Wire Products

| **Phone:** 610-863-2250

| **Email Us**

LASHING WIRE

Century Wire Products Corp. is the finest producers of stainless steel lashing wire.

Century Wire Products Corp, has dedicated itself to bringing you the highest quality lashing wire, guy strand and stainless steel cable to the CATV and Telecom industries. We partner with our customers and suppliers as well to bring you the best product you can find.

We have in stock all major sizes and can usually ship with in 24 hours. Made to order products are available upon your request. Once you use our wire, you will be back for more!

Not only does Century Wire Products Corp. Manufacture lashing wire rope, we also have guy strand which is manufactured to our specifications.

We are also distributors for all **General Machine Products**.

Our warehouses cover the 48 states and Puerto Rico.

Lashing Wire Grade Types

Type 430 (S43000)

This is a magnetic thermally nonhardening ferritic stainless steel alloy containing 16-18% chromium with no nickel or molybdenum rendering it susceptible to corrosion attack.

Type 302 (S30200)

This is an austenitic nonmagnetic and thermally nonhardening stainless steel. Corrosion and oxidation resistance is provided by the 18-20% chromium and the 8% min. nickel content.

Type 316 (S31600)

This is also austenitic, nonmagnetic and thermally nonhardening stainless steel. In comparison to type 302, the nickel content is increased from 8% to 10% and includes the addition of up to 3% molybdenum.

All lashing wire rope is manufactured in the USA in accordance with standard specifications for lashing wire and can be certified upon request.

Other wire sizes and alloys can be quoted upon request.

Product Specifications:

Part No.	Type	Size	Temper	Tensile Strength	Avg Break
.038SS302ACW	302	.038	Annealed	95,000 - 125,000 PSI	115 lbs.
.045SS302ACW	302	.045	Annealed	95,000 - 125,000 PSI	165 lbs.
.045SS430ACW	430	.045	Annealed	70,000 - 95,000 PSI	125 lbs.
.045SS316ACW	316	.045	Annealed	95,000 - 120,000 PSI	145 lbs.

Packaging:

Part No.	Ft/Coil	W.T. Coil	Wt/box of 6
.038SS302ACW	1,600	6.3	37 lbs
.045SS302ACW	1,200	6.5	40 lbs.
.045SS430ACW	1,200	6.5	40 lbs.
.045SS316ACW	1,200	6.5	40 lbs.

Straight hub or tapered hub are available.

All weights and footage lengths are approximate. There are six (6) coils per box with total box weight described above. Footages length are plus/minus 30 ft. Pallet quantity is 378 coils or 63 boxes.

Contact Us

Call today for a quote and delivery on any of
the products shown on our web site.
(610) 863-2250

[Century Wire Products](#) | [About Us](#) | [News](#) | [Contact Us](#)
[Stainless Steel, Galvanized & Annealed Wire](#) | [Lashing](#) | [Stranded](#) | [Tie & Lock](#)

© 2004-2009 Century Wire Products | 153 8th Street Wind Gap, PA 18091 | Phone: 610 863-2250 | [Privacy Policy](#)

Developed by Computer Images Web, LLC